DT-1 Series Electronic Theodolite

Features:

- Special design: single horizontal spindle which cross telescope New design concept, combine higher precision, better stable and shock resistance ability.
- Absolute angle encoder system
 Able to read angle data without passing "0", let angle measurement be more simple and convenient.
- English large display
 Adopt backlight technology, able to display horizontal and vertical angle at the same time. Convenient to be used in different condition.
- Superior water and dust proof specification IP66
 Able to prevent dust and humid air, maintain good performance even in bad environment.

Specification:

Model No.:	DT-21 / DT-51
Telescope	
Image	Erect
Magnification	30X
Objective aperture	45mm
Field of view	1° 30'
Shortest viewing distance	1.4m
Stadia ratio	100
Resolution	3"

Angle measurement

Angle measurement mode Absolute angle encoder system

Minimum count 1" / 5"

Accuracy 2" / 5"

Angle units DEG/MIL/GON

Display LCD double sides

Compensation range

Plummet Laser or optical plummet for option

± 3'

Precision of plate vial 30" / 2mmPrecision of circular vial 8' / 2mmWorking temperature $-20^{\circ}\text{C} \sim 50^{\circ}\text{C}$

Battery 3.7V chargeable lithium battery

Weight 4.8kg

Standard outfit:

main unit, 1pc rechargeable battery pack and charger, instrument manual, plastic case.



